

## Application

Optimal carries two styles of Zero Fibre Tubing, both used to protect fragile bare fibres when breaking out loose tube cables.

Two sizes are available to emulate corded or tight buffer constructions.

For corded application the construction consists of a 2mm PVC outer jacket, a 0.9mm inner tube, and aramid yard for tensile strength.

Tight buffer style use a clear PE tube and will fit most standard connectors. The clear tubing allows the fibre colours to be visible allowing easy identification of individual fibre colours

## Features

- 1.8mm & 0.9mm diameters to suit most common connector types
- 1.8mm cord available in a variety of colours
- Clear 0.9mm tube allows easy identification of fibre colours



## Specifications

### 1.8mm Corded ZFT

Jacket Material / Diameter	PVC / 1.8mm
Inner Tube Material / Diameter	Nylon / 0.9mm OD, 0.35mm ID
Tensile Rating	220N
Operating Temperature	-20°C to +75°C

### 0.9mm Clear ZFT

Tube Material / Diameter	PE / 0.92mm OD, 0.42mm ID
Operating Temperature	-20°C to +75°C

## Ordering Details

OPT-ZFT-9	0.9mm Zero Fibre Tubing - Clear (100m roll)
OPT-ZFT-2-YW	1.8mm Zero Fibre Tubing - Yellow
OPT-ZFT-2-OE	1.8mm Zero Fibre Tubing - Orange
OPT-ZFT-2-AQ	1.8mm Zero Fibre Tubing - Aqua
OPT-ZFT-2-xx	Other colours on request (MOQ applies)

### Optimal Cable Services Pty. Ltd.

100 Olympia Street  
 Tottenham, Victoria, 3012

Ph: 03 9316 8300 / Fax: 03 9314 1722

Email: [sales@optimal.com.au](mailto:sales@optimal.com.au)  
 Web: [www.optimal.com.au](http://www.optimal.com.au)

### Cable & Connectivity Sales

Vic : 0430 494 022 - Murray Meltzer  
 : 0412 361 281 - Paul Cross

NSW : 0400 122 738 - Mike Cotie  
 : 0422 651 321 - Martin Prendergast

Qld : 0414 701 292 - Eric Brace  
 : 0407 630 429 - Ian Lee

WA : 0407 630 429 - Ian Lee

SA : 0412 361 281 - Paul Cross

Tas : 0430 494 022 - Murray Meltzer

NZ : +61-412-361-281 - Paul Cross